

Technical Specification

C Type Power Press

Specification	3	5	5	10	10	10	15	20	20	30	30	50	60	75	85	100	150	200	250	300
CRANK DIAMETER	38	51	51	60	60	60	70	76	76	83	83	95	101	115	115	127	140	158	165	175
STROKE ADJUSTMENT	2-19 MM	6-25 MM	6-38 MM	6-25 MM	6-51 MM	6-51 MM	10-51 MM	13-51 MM	13-76 MM	13-63 MM	13-89 MM	13-76 MM	13-80 MM	13-102 MM	13-102 MM	13-115 MM	13-127 MM	13-152 MM	13-165 MM	13-175 MM
SLIDE ADJUSTMENT	20	25	25	25	25	25	25	25	25	25	25	40	40	50	50	60	60	70	70	70
HOLE IN RAM	19	25	25	25	25	25	32	32	32	38	38	51	51	51	51	55	55	63	63	63
HOLE IN BED	51	63	75	76	76	76	89	89	89	102	102	127	127	178	178	191	203	216	216	228
L x W OF BED	255 X 152	305 x 178	356 x 203	356 x 203	406 x 254	406 x 254	457 x 305	457 x 305	508 x 355	508 x 355	559 x 406	660 x 406	711 x 508	711 x 508	760 x 595	813 x 558	914 x 610	965 x 660	1067 x 711	1117x762
DIST. BED TO RAM	140	152	175	180	205	205	230	230	254	266	305	290	320	330	350	381	410	432	485	508
STROKE/Mill	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
DOUBLE GEAR (SPM)	-	-	-	-	-	-	-	50	50	40	40	30	-	-	-	-	-	-	-	-
SINGLE GEAR (SPM)	90	80	80	80	80	80	75	60	60	55	55	50	50	40	40	30	30	30	30	30
UN GEAR (SPM)	165	150	150	130	130	130	120	120	120	115	115	90	-	-	-	-	-	-	-	-
H. P./ RPM (UG)	0.5 / 960	0.5/960	0.5 / 960	1/960	1-960	1/960	1.5/960	2/960	2/960	3/960	3/960	5/960	-	-	-	-	-	-	-	-
H. P./RPM (G)	0.5/1440	0.5/1440	0.5/1440	1/1440	1/1440	1/1440	1.5/1440	2/1440	2/1440	3/1440	3/1440	5/1440	5/1440	7.5/1440	7.5/1440	10/1440	15/1440	20/1440	25/1440	30/1440
FLOOR TO TOP OF BED	520	690	690	730	730	730	740	815	844	815	856	900	900	915	915	915	915	915	915	915
WT.III KGS (APPOX)	150	300	350	450	525	525	700	900	1050	1100	1465	2250	2700	3500	4050	5500	6000	9500	11500	13000