

Technical Specification

High Speed Presses – C Type

High Speed Presses KVH - Series

MODEL			KVH - 16			KVH - 25			KVH - 40			KVH - 63	
CAPACITY		TON/KN	16 / 160			25 / 250			40 / 400			60 / 630	
Rated Distance		mm	1.2			1.6			1.6			2	
Stroke Length		mm	10	20	30	10	20	30	10	20	30	20	30
No. of Stroke Per Minute		SPM	150-650	150-600	150-600	150-550	150-550	150-550	150-550	150-550	150-450	150-400	150-350
Shut weight		mm	210	205	200	220	215	210	265	260	255	325	320
Slide Face	F.B.	mm	140			158			290			340	
	L.R.	mm	250			260			340			420	
Slide Adjustment		mm	50			60			50			50	
Opening in	Dia	mm	40			40			50			50	
Slide	Depth	mm	60			75			75			75	
Depth of Throat		mm	150			155			235			270	
Bolster	F.B.	mm	290			300			450			520	
Surface	L.R.	mm	480			500			740			850	
Bed Opening	F.B.	mm	80			80			120			130	
	L.R.	mm	150			150			300			300	
Dist. Between Uprights		mm	275			300			325			350	
Bolster Thickness		mm	60			75			110			120	
Main Motor		Hp / Kw	3 / 2.2			5 / 3.5			7.5 / 5.5			15 / 11	
Air Pressure		Kg / Cm ²	5.5			5.5			5.5			5.5	

NOTE: As day to day improvements are contemplated we reserve the right to change specification/design without prior notice.