

## Technical Specification

### KH4P Series Hydraulic Press

Parameter		Unit	40	63	100	100	160	160	200	315	400	500	500	630	800	1000	1250	1600	2000
Rated pressure		KN	400	630	1000	1000	1600	1600	2000	3150	4000	5000	5000	6300	8000	10000	12500	16000	20000
Stoke of slide		mm	450	500	600	600	700	700	700	800	800	900	900	900	900	900	900	900	1300
Stoke of knock-out		mm	150	200	200	200	200	200	250	300	300	350	350	350	350	400	400	400	500
Distance between		mm	700	750	880	880	900	1000	1100	1250	1250	1500	1500	1500	1500	1600	1600	1600	1800
Slide	Approach	mm/s	100	100	100	100	100	100	100	100	100	100	100	100	75	75	75	60	60
Speed	Pressing	mm/s	8	8	6	6	6	6	6	5	5	5	5	5	5	4	4	4	4
+/-15%	Rectum	mm/s	120	120	100	100	100	100	100	100	100	100	100	100	75	75	75	60	60
Effective	L-R	mm	500	580	720	720	680	1000	1000	1260	1240	1400	2400	1500	1500	1580	1700	2000	3200
working table	F-B	mm	460	500	580	700	620	800	900	1200	1200	1400	1400	1500	1400	1600	1600	1600	2200
Knockout pressure		KN	120	190	190	190	400	400	400	630	630	1000	1000	1000	1600	2000	2000	2000	3200
Overall	L-R	mm	2000	2400	2500	2700	2700	2800	3100	3235	3235	4060	6500	4200	4800	5250	5250	5800	4500
Dimension	F-B	mm	1300	1400	1500	1600	1700	1700	1800	2060	2200	3520	3800	4200	4000	3800	3800	4000	3200
	Height	mm	2600	3100	2950	2950	3400	3400	3500	4295	4500	4995	4740	5600	6000	6800	7000	6200	7200
Motor power		KW	3.5	5.5	7.5	7.5	10	10	15	17	20	27	27	33	40	47	53	57	80