

Technical Specification

NC / CNC Series

Sr. No.	KAWA Model No.	Shear Length In mm	Shearing Capacity Thickness In mm		Back Gauge Strock	Working Cycle Minute	Adjustment Rake Angle	Motor HP/KW	Length In mm A	Width In mm B	Height In mm C	Grounded PIT D
			M.S UTS 45kgs/mm ²	M.S UTS 65kgs/mm ²								
1	20/6	2050	4/6	3/4	750	30-15	1°-2.30°	7.5/5.5	2650	1500	1800	NA
2	20/8	2050	6/8	4/6	750	30-15	1°-2.30°	10/7.5	2650	1600	1900	NA
3	20/10	2050	8/10	6/8	750	25-10	1°-3°	15/11	2700	1700	2150	NA
4	20/13	2050	10/13	8/10	750	25-10	1°-3°	20/15	2800	2050	2150	NA
5	20/16	2050	13/16	10/13	900	16-10	1°-3.30°	25/18.75	2850	2050	2200	NA
6	20/18	2050	16/18	13/16	900	16-10	1°-3.30°	30/22.5	2900	2050	2300	NA
7	20/22	2050	18/20	16/18	900	12-8	1°-3.30°	35/26	2950	2100	2410	NA
8	20/25	2050	3/4	18/20	900	12-8	1°-4°	40/30	3000	2150	2550	300
9	25/6	2050	4/6	3/4	750	25-10	1°-2.30	7.5/5.5	3000	1500	1800	NA
10	25/8	2050	6/8	4/6	750	24-10	1°-2.30°	10/7.5	3000	1600	1900	NA
11	25/10	2050	8/10	6/8	750	20-9	1°-3°	15/11	3000	1700	2150	NA
12	25/13	2050	10/13	8/10	750	14-8	1°-3°	20/15	3200	2050	2200	NA
13	25/16	2050	13/16	10/13	900	14-6	1°-3.30°	25/18.75	3250	2050	2200	NA
14	25/18	2050	16/18	13/16	900	14-6	1°-3.30°	30/22.5	3250	2050	2450	NA
15	25/22	2050	18/22	16/18	900	14-5	1°-3.30°	35/26	3300	2100	2550	300
16	25/22	2050	22/25	18/20	900	13-5	1°-4°	40/30	3350	2150	2550	400
17	25/25	3050	4/6	3/4	750	24-10	1°-2.30°	10/7.5	3600	1500	1850	NA
18	30/8	3050	6/8	4/6	750	24-10	1°-2.30°	15/11	3710	1600	1950	NA
19	30/10	3050	8/10	6/8	750	18-8	1°-3°	20/15	3700	1700	2200	NA
20	30/13	3050	10/13	8/10	750	12-6	1°-3°	20/15	3750	2050	2250	NA
21	30/16	3050	13/16	10/13	900	12-5	1°-3.30°	25/18.75	3800	2050	2450	NA
22	30/18	3050	16/18	13/16	900	12-5	1°-3.30°	30/22.5	3850	2050	2500	250
23	30/22	3050	18/22	16/18	900	12-5	1°-3.30°	35/26	3850	2100	2550	500
24	30/25	3050	22/25	18/20	900	10-4	1°-4°	40/30	3900	2150	2550	660
25	40/6	4050	4/6	3/4	750	24-10	1°-2.30°	10/7.5	4600	1500	1900	NA
26	40/8	4050	6/8	4/6	750	20-10	1°-2.30°	20/15	4650	1600	2050	200
27	40/10	4050	8/10	6/8	750	18-8	1°-3°	30/22.5	4650	1700	2250	300
28	40/13	4050	10/13	8/10	750	12-6	1°-3°	30/22.5	4700	2050	2400	400
29	40/16	4050	13/16	10/13	900	10-4	1°-3.30°	25/18.75	4700	2050	2480	500
30	40/18	4050	16/18	13/16	900	10-4	1°-3.30°	30/22.5	4700	2050	2520	600
31	40/22	4050	18/22	16/18	900	10-4	1°-3.30°	35/26	4800	2100	2620	650
32	40/25	4050	22/25	18/20	900	8-3	1°-4°	40/30	4850	2150	2620	730