

Technical Specification

Pillar Type Power Press

Specification	20	20	30	30	50	75	100	150	200	250	300
CRANK DIAMETER	76	76	83	83	95	114	127	140	158	165	175
STROKE ADJUSTMENT	13-51 MM	13-76 MM	13-63 MM	13-89 MM	13 -76 MM	13-102 MM	13-115 MM	13-127 MM	13-152 MM	13-165 MM	13-177 MM
SLIDE ADJUSTMENT	25	25	25	25	40	50	60	60	70	70	70
HOLE IN RAM	32	32	38	38	51	51	55	55	63	63	63
HOLE IN BED	89	89	102	102	127	178	191	203	216	216	228
L x W OF BED	406 X 508	406 X 508	457 X 556	457 X 556	508x 610	610x762	660 x813	711 X914	762 x 965	812x1016	863 x 1066
DIST. BED TO RAM	230	255	266	305	290	330	381	410	432	485	508
STROKE / MIN	-	-	-	-	-	-	-	-	-	-	-
DOUBLE GEAR (SPM)	50	50	40	40	30	-	-	-	-	-	-
SINGLE GEAR (SPM)	60	60	55	55	50	40	30	30	30	30	30
UN GEAR (SPM)	120	120	115	45	-	-	-	-	-	-	-
H. P./RPM (UG)	2/960	2/960	3/960	3/960	-	-	-	-	-	-	-
H. P./ RPM (G)	2/1440	2/1440	3/1440	3/1440	5/1440	7.5/1440	10/1440	15/1440	20/1440	25/1440	30/1440
FLOOR TO TOP OF BED	815	815	815	815	900	915	915	915	915	915	915
WT.IN KGS (APPOX)	800	1050	1000	1300	2000	3100	4600	5650	9000	11500	12500